

View Online at <https://aerobasegroup.com/nsn/4330-01-317-2022>

Mounting Type:

Unthreaded hole head side

Mounting Hole Diameter:

0.270 inches

Mounting Hole Quantity:

2

Body Length:

2.900 inches

Body Outside Diameter:

4.090 inches

Body Height:

5.650 inches

Filtration Rating In Microns:

3.0 absolute

Drop Pressure:

19.0 pounds per square inch

Differential Pressure:

50.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator and thermal lockout

Filtering Element Quantity:

1

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow or by-pass flow

Special Features:

Visual indicator w/manual reset

Material:

Aluminum bodyfiber synthetic filtering medium and resin synthetic filtering mediumrubber buna n sealaluminum sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000