NSN 4330-01-319-3543

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-319-3543

| view Online at https://acrobasegroup.com/nsi//4000-01-019-0040 |
|--|
| Mounting Type: |
| Inlet connection line and outlet connection line |
| Body Length: |
| 7.860 inches |
| Body Height: |
| 8.590 inches |
| Design Type: |
| Reusable |
| Features Provided: |
| By-pass valve |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch |
| Filtering Media Design: |
| Pleated single filtering media response |
| First Intake Connection Type: |
| Threaded internal pipe bottom side |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical |
| First Discharge Connection Type: |
| Threaded internal pipe top |
| First Intake Thread Series Designator: |
| Nptf |
| First Discharge Thread Series Designator: |
| Nptf |
| First Intake Thread Size: |
| 1.250 inches |
| First Discharge Thread Size: |
| 1.250 inches |
| First Intake Thread Direction: |
| Right-hand |
| First Discharge Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Special Features: |
| W/74 micron filtration |
| Material: |
| Rubber seal |

Media For Which Designed: Fuel/oil, hydrocarbon

NSN 4330-01-319-3543

Fluid Filter - Page 2 of 2



| Style | De | sia | nato | ١r٠ |
|-------|-----|------|------|------------|
| OLYIC | De. | oig: | IIau | <i>,</i> , |

High pressure bolted shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000