NSN 4330-01-321-6486

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-321-6486 | | | | | |
|---|--|--|--|--|--|
| Mounting Type: | | | | | |
| Inlet connection line and outlet connection line | | | | | |
| Body Outside Diameter: | | | | | |
| 5.000 inches | | | | | |
| Body Height: | | | | | |
| 10.630 inches | | | | | |
| Filtration Rating In Microns: | | | | | |
| 1.0 absolute | | | | | |
| Drop Pressure: | | | | | |
| 5.0 pounds per square inch | | | | | |
| Design Type: | | | | | |
| Reusable | | | | | |
| Tempurature Rating: | | | | | |
| 175.0 degrees fahrenheit | | | | | |
| Features Provided: | | | | | |
| Drain cock | | | | | |
| Filtering Element Quantity: | | | | | |
| 1 | | | | | |
| Maximum Operating Pressure: | | | | | |
| 250.0 pounds per square inch | | | | | |
| Filtering Media Design: | | | | | |
| Porous single filtering media response | | | | | |
| First Intake Connection Type: | | | | | |
| Threaded internal pipe head side | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | |
| Identical to first intake connection | | | | | |
| First Intake Thread Series Designator: | | | | | |
| Nptf | | | | | |
| First Intake Thread Size: | | | | | |
| 1.500 inches | | | | | |
| First Intake Thread Direction: | | | | | |
| Right-hand | | | | | |
| Filtering System For Which Designed: | | | | | |
| Full flow | | | | | |
| Special Features: | | | | | |
| Manual drain; 100 scfm element air flow rate | | | | | |
| Material: | | | | | |
| Rubber buna n seal | | | | | |
| Media For Which Designed: | | | | | |
| Air | | | | | |

Style Designator:

High pressure threaded body

NSN 4330-01-321-6486

Fluid Filter - Page 2 of 2



| - | | | |
|----|----|-----|------|
| ٠. | hΔ | Iŧ. | ife: |
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000