

View Online at <https://aerobasegroup.com/nsn/4330-01-324-2166>

**Mounting Type:**

Unthreaded hole head side

**Mounting Hole Diameter:**

0.270 inches

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

4.000 inches

**Body Width:**

2.900 inches

**Body Height:**

6.510 inches

**Filtration Rating In Microns:**

15.0 absolute

**Drop Pressure:**

0.9 pounds per square inch

**Differential Pressure:**

100.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

3.120 inches

**Design Type:**

Reusable

**Tempurature Rating:**

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

Differential pressure indicator

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Visual indicator w/manual reset, thermal limits-32.0deg to 80.0deg f

**Material:**

Aluminum bodyrubber buna n sealaluminum sediment bowl

**Media For Which Designed:**

Fuel/oil, hydrocarbon or water/alcohol mixture

**Surface Treatment:**

Anodize bodyanodize sediment bowl

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000