

View Online at <https://aerobasegroup.com/nsn/4330-01-324-2166>

Mounting Type:

Unthreaded hole head side

Mounting Hole Diameter:

0.270 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

4.000 inches

Body Width:

2.900 inches

Body Height:

6.510 inches

Filtration Rating In Microns:

15.0 absolute

Drop Pressure:

0.9 pounds per square inch

Differential Pressure:

100.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

Design Type:

Reusable

Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Visual indicator w/manual reset, thermal limits-32.0deg to 80.0deg f

Material:

Aluminum bodyrubber buna n sealaluminum sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon or water/alcohol mixture

Surface Treatment:

Anodize bodyanodize sediment bowl

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000