

View Online at <https://aerobasegroup.com/nsn/4330-01-335-0417>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.562 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

5.500 inches

Body Width:

5.500 inches

Body Height:

14.562 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

12.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.000 inches

Design Type:

Reusable

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator and drain plug

Filtering Element Quantity:

1

Maximum Operating Pressure:

2500.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

1.250 inches

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.625 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Inverted design, head on bottom, container has steel cap; electric seitch dirt alarm

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000