

View Online at <https://aerobasegroup.com/nsn/4330-01-335-0421>

Mounting Type:

Bracket w/drilled hole center and strap center

Mounting Hole Diameter:

0.420 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

7.810 inches

Body Height:

15.690 inches

Filtration Rating In Microns:

25.0

Drop Pressure:

6.5 pounds per square inch

Distance Between Mounting Hole Centers:

Between 3.500 inches and 7.000 inches

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator and drain plug

Bracket Quantity:

1

Filtering Element Quantity:

1

Maximum Operating Pressure:

400.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded internal tube bottom

First Intake Thread Series Designator:

Un

First Discharge Thread Series Designator:

Un

First Intake Thread Size:

2.500 inches

First Discharge Thread Size:

2.500 inches

First Intake Thready Qty Per Inch (tpi):

12

First Discharge Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Discharge Thread Class:

3b

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

2 mounting straps provided

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Anodize container/cartridge

Style Designator:

EII type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000