

View Online at <https://aerobasegroup.com/nsn/4330-01-335-0421>

**Mounting Type:**

Bracket w/drilled hole center and strap center

**Mounting Hole Diameter:**

0.420 inches

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

7.810 inches

**Body Height:**

15.690 inches

**Filtration Rating In Microns:**

25.0

**Drop Pressure:**

6.5 pounds per square inch

**Distance Between Mounting Hole Centers:**

Between 3.500 inches and 7.000 inches

**Design Type:**

Reusable

**Temperature Rating:**

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

Air bleed valve and by-pass valve and differential pressure indicator and drain plug

**Bracket Quantity:**

1

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

400.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Not identical

**First Discharge Connection Type:**

Threaded internal tube bottom

**First Intake Thread Series Designator:**

Un

**First Discharge Thread Series Designator:**

Un

**First Intake Thread Size:**

2.500 inches

**First Discharge Thread Size:**

2.500 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Discharge Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

3b

**First Discharge Thread Class:**

3b

**First Intake Thread Direction:**

Right-hand

**First Discharge Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

2 mounting straps provided

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Anodize container/cartridge

**Style Designator:**

EII type (hydraulic)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000