NSN 4330-01-339-1620

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-339-1620

Mounting Type:
Threaded hole head
Mounting Hole Quantity:
4
Body Outside Diameter:
4.000 inches
Body Width:
3.710 inches
Body Height:
11.930 inches
Filtration Rating In Microns:
9.0
Drop Pressure:
5.0 pounds per square inch
Differential Pressure:
25.0 pounds per square inch
Distance Between Mounting Hole Centers:
1.380 inches and 1.380 inches
Design Type:
Reusable
Features Provided:
Differential pressure indicator and by-pass valve
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
150.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.375 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.000 inches
First Intake Thready Qty Per Inch (tpi):
12
First Intaka Throad Class

3b

NSN 4330-01-339-1620

Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
By-pass flow or full flow
Special Features:
Spin-on type; visual lh indicator; cast alum head
Material:
Aluminum body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Unthreaded shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A24000