

View Online at <https://aerobasegroup.com/nsn/4330-01-339-1620>

Mounting Type:

Threaded hole head

Mounting Hole Quantity:

4

Body Outside Diameter:

4.000 inches

Body Width:

3.710 inches

Body Height:

11.930 inches

Filtration Rating In Microns:

9.0

Drop Pressure:

5.0 pounds per square inch

Differential Pressure:

25.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.380 inches and 1.380 inches

Design Type:

Reusable

Features Provided:

Differential pressure indicator and by-pass valve

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

150.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.000 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

By-pass flow or full flow

Special Features:

Spin-on type; visual lh indicator; cast alum head

Material:

Aluminum body

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000