

View Online at <https://aerobasegroup.com/nsn/4330-01-339-7970>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.562 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

6.250 inches

Body Height:

25.000 inches

Filtration Rating In Microns:

10.0

Differential Pressure:

25.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.500 inches and 5.000 inches

Design Type:

Nonreusable

Temperature Rating:

300.0 degrees fahrenheit

Features Provided:

Drain plug and by-pass valve and air bleed valve

Filtering Element Quantity:

2

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated all filtering media responses

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

1.250 inches

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.875 inches

First Intake Thread Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

By-pass flow or full flow

Special Features:

Dirt alarm and cap

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000