NSN 4330-01-341-2428

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole head

Mounting Hole Quantity:

3

Body Length:

5.500 inches

Body Width:

5.340 inches

Body Height:

9.000 inches

Filtration Rating In Microns:

3.0 absolute

Drop Pressure:

6.0 pounds per square inch

Differential Pressure:

100.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 3.200 inches and 3.850 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Tempurature Rating:

Between -20.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Un

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.516 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

8.040 inches



NSN 4330-01-341-2428

Fluid Filter - Page 2 of 2



First Intake Thread Series Designator:

Unf

First Intake Thread Size:

1.3125 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Material:

Aluminum alloy bodysteel container/cartridgeany acceptable filtering mediumplastic seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Enamel container/cartridge and paint container/cartridge

Style Designator:

Tee type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000