## NSN 4330-01-341-2428

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-341-2428

Mounting Type:
Threaded hole head
Mounting Hole Quantity:
3
Body Length:
5.500 inches
Body Width:
5.340 inches
Body Height:
9.000 inches
Filtration Rating In Microns:
3.0 absolute
Drop Pressure:
6.0 pounds per square inch
Differential Pressure:
100.0 pounds per square inch
Distance Between Mounting Hole Centers:
Between 3.200 inches and 3.850 inches
Mounting Facility Thread Direction:
Right-hand
Design Type:
Reusable
Tempurature Rating:
Between -20.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Un
Maximum Operating Pressure:
150.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.516 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection

8.040 inches

**Distance From Bottom Of Body To Center Of Inlet:** 

## **NSN 4330-01-341-2428** Fluid Filter - Page 2 of 2



First Intake Thread Series Designator:
Unf
First Intake Thread Size:
1.3125 inches
First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Material:
Aluminum alloy bodysteel container/cartridgeany acceptable filtering mediumplastic seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Surface Treatment:
Enamel container/cartridge and paint container/cartridge
Style Designator:
Tee type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000