

View Online at <https://aerobasegroup.com/nsn/4330-01-343-3687>

**Mounting Type:**

Inlet connection head side and outlet connection head side

**Filtration Rating In Microns:**

74.0 absolute

**Design Type:**

Reusable

**Temperature Rating:**

Between -45.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Unit Quantity:**

2

**Features Provided:**

Antidrain back device and switch-over valve and air bleed valve and by-pass valve and differential pressure relief valve

**Filtering Element Quantity:**

4

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Filtering Media Design:**

Mesh single filtering media response

**First Intake Connection Type:**

Plain face flange head side

**Second Intake Connection Relationship To First Intake Connection:**

Identical

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**Second Discharge Connection Relationship To Preceding Connection:**

Identical to first intake connection

**First Intake Flange Shape Style:**

Rectangular w/unthreaded bolt holes

**First Intake Flange Face Style:**

Plain

**First Intake Flange Thickness:**

1.190 inches

**First Intake Flange Length:**

4.062 inches

**First Intake Flange Width:**

3.110 inches

**Filtering System For Which Designed:**

By-pass flow or full flow

**Special Features:**

Ports 2.0in.Nptf flange; 25psi bypass and indicator setting; manual handle points to filter in service; change-over valve has 1/4-18npt drian vent, double bowl of hot-rolled steel 0.120in wall nom.: 29.04in.O/a ht, 21.25in.O/a wt: 13.62in.O/a dp

**Material:**

Steel container/cartridge

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Anodize body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000