NSN 4330-01-343-8536

Fluid Filter Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-343-8536 |
|--|
| Mounting Type: |
| Inlet connection head and outlet connection head |
| Drop Pressure: |
| 35.0 pounds per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| 40.0 degrees celsius |
| Unit Quantity: |
| 2 |
| Features Provided: |
| Drain plug |
| Filtering Element Quantity: |
| 2 |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Filtering Media Design: |
| Porous single filtering media response |
| First Intake Connection Type: |
| Plain face flange head |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Flange Shape Style: |
| Round w/threaded bolt holes |
| First Intake Flange Face Style: |
| Recessed |
| First Intake Flange Thickness: |
| 0.750 inches |
| First Intake Flange Recess Diameter: |
| 2.125 inches |
| First Intake Flange Recess Depth: |
| 0.312 inches |
| Filtering System For Which Designed: |
| By-pass flow or full flow |
| Special Features: |
| Left hand outlet (can be used to support ssbn 726 lh outlet application) |
| Material: |
| Rubber synthetic seal |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Shelf Life: |

N/a

NSN 4330-01-343-8536

Fluid Filter Assembly - Page 2 of 2



| | | | ıre: |
|--|--|--|------|
| | | | |

--

Demilitarization:

No

Fiig:

A24000