

View Online at <https://aerobasegroup.com/nsn/4330-01-343-8537>

**Mounting Type:**

Inlet connection head and outlet connection head

**Drop Pressure:**

35.0 pounds per square inch

**Design Type:**

Reusable

**Temperature Rating:**

Between 20.0 degrees celsius and 60.0 degrees celsius

**Unit Quantity:**

2

**Filtering Element Quantity:**

2

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Porous single filtering media response

**First Intake Connection Type:**

Plain face flange head

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Flange Shape Style:**

Round w/threaded bolt holes

**First Intake Flange Face Style:**

Recessed

**First Intake Flange Thickness:**

0.750 inches

**First Intake Flange Recess Diameter:**

2.125 inches

**First Intake Flange Recess Depth:**

0.312 inches

**Filtering System For Which Designed:**

By-pass flow or full flow

**Special Features:**

No bypass relief; standard right hand outlet; both ports 8 hole flange 1/2-20unf-3b thd 3/4 dp 90.0deg csk; o/a 21.500in.H, o/a 18.000in.W, o/a 10.060in.D

**Material:**

Rubber synthetic seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Supplementary Features:**

4holes 1/2-20unf-3b thd 0.800 depth located on bottom of head between element bowls

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000