

View Online at <https://aerobasegroup.com/nsn/4330-01-343-8537>

Mounting Type:

Inlet connection head and outlet connection head

Drop Pressure:

35.0 pounds per square inch

Design Type:

Reusable

Temperature Rating:

Between 20.0 degrees celsius and 60.0 degrees celsius

Unit Quantity:

2

Filtering Element Quantity:

2

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Porous single filtering media response

First Intake Connection Type:

Plain face flange head

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Round w/threaded bolt holes

First Intake Flange Face Style:

Recessed

First Intake Flange Thickness:

0.750 inches

First Intake Flange Recess Diameter:

2.125 inches

First Intake Flange Recess Depth:

0.312 inches

Filtering System For Which Designed:

By-pass flow or full flow

Special Features:

No bypass relief; standard right hand outlet; both ports 8 hole flange 1/2-20unf-3b thd 3/4 dp 90.0deg csk; o/a 21.500in.H, o/a 18.000in.W, o/a 10.060in.D

Material:

Rubber synthetic seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Supplementary Features:

4holes 1/2-20unf-3b thd 0.800 depth located on bottom of head between element bowls

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000