

View Online at <https://aerobasegroup.com/nsn/4330-01-346-9879>

Mounting Type:

Inlet connection head side and outlet connection head side

Mounting Hole Quantity:

4

Body Outside Diameter:

6.500 inches

Body Height:

24.520 inches

Filtration Rating In Microns:

10.0 absolute

Differential Pressure:

50.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.437 inches and 3.125 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Temperature Rating:

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and drain plug and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

5000.0 pounds per square inch

Filtering Media Design:

Molded single filtering media response

First Intake Connection Type:

Plain face flange head side

Mounting Facility Thread Size:

0.625 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Length:

2.620 inches

First Intake Flange Width:

4.000 inches

Filtering System For Which Designed:

Full flow

Special Features:

Bottom base mounted bowl-up design; hex wrenching facility on lid; double element length size; visual indicator on left side

Material:

Stainless steel sediment bowl

Material Specification:

Astm a-536, 80-55-06 assn standard single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000