

View Online at <https://aerobasegroup.com/nsn/4330-01-347-0861>

Mounting Type:

Unthreaded hole bottom

Mounting Hole Diameter:

0.562 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

6.250 inches

Body Height:

15.750 inches

Filtration Rating In Microns:

3.0 absolute

Differential Pressure:

40.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.500 inches and 5.000 inches

Design Type:

Reusable

Temperature Rating:

225.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator and drain plug

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Woven 2nd filtering media response or pleated 2nd filtering media response

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

1.500 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Base mounted bowl-up design w/ threaded lid; electric cam operated dirt alarm; filter media microglass pleated w/expoxy coated steel fabric

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000