NSN 4330-01-347-0861

Fluid Filter - Page 1 of 2

Mounting Type:

Special Features:



View Online at https://aerobasegroup.com/nsn/4330-01-347-0861

Unthreaded hole bottom
Mounting Hole Diameter:
0.562 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
6.250 inches
Body Height:
15.750 inches
Filtration Rating In Microns:
3.0 absolute
Differential Pressure:
40.0 pounds per square inch
Distance Between Mounting Hole Centers:
4.500 inches and 5.000 inches
Design Type:
Reusable
Tempurature Rating:
225.0 degrees fahrenheit
Features Provided:
Air bleed valve and by-pass valve and differential pressure indicator and drain plug
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
Filtering Media Design:
Woven 2nd filtering media response or pleated 2nd filtering media response
First Intake Connection Type:
Threaded internal pipe head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
1.500 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow

Base mounted bowl-up design w/ threaded lid; electric cam operated dirt alarm; filter media microglass pleated w/expoxy coated steel fabric

NSN 4330-01-347-0861

Fluid Filter - Page 2 of 2



ΝЛ	2+	er	in	١.
IVI	aı	ŒI.	a	ı .

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000