

View Online at <https://aerobasegroup.com/nsn/4330-01-352-0049>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

6

Body Outside Diameter:

5.250 inches

Body Height:

12.270 inches

Filtration Rating In Microns:

33.0

Differential Pressure:

15.0 pounds per square inch

Distance Between Mounting Hole Centers:

0.750 inches and 0.750 inches and 1.880 inches

Design Type:

Nonreusable

Tempurature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

200.0 pounds per square inch

Filtering Media Design:

Pleated 1st filtering media response

First Intake Connection Type:

Threaded internal pipe head side

Second Intake Connection Relationship To First Intake Connection:

Identical

Mounting Facility Thread Size:

0.312 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

1.250 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

50.0gpm; hex wrenching device on bottom; indicator ports 1 and 4

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Zinc container/cartridge

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000