

View Online at <https://aerobasegroup.com/nsn/4330-01-352-0049>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

6

**Body Outside Diameter:**

5.250 inches

**Body Height:**

12.270 inches

**Filtration Rating In Microns:**

33.0

**Differential Pressure:**

15.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

0.750 inches and 0.750 inches and 1.880 inches

**Design Type:**

Nonreusable

**Tempurature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Filtering Media Design:**

Pleated 1st filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Second Intake Connection Relationship To First Intake Connection:**

Identical

**Mounting Facility Thread Size:**

0.312 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Npt

**First Intake Thread Size:**

1.250 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

50.0gpm; hex wrenching device on bottom; indicator ports 1 and 4

**Material:**

Steel container/cartridge

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Zinc container/cartridge

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000