## NSN 4330-01-356-6877

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-356-6877

Mounting Type:
Unthreaded hole head
Mounting Hole Diameter:
0.339 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
4.094 inches
Body Height:
6.102 inches
Filtration Rating In Microns:
2.5 absolute
Distance Between Mounting Hole Centers:
Between 1.252 inches and 3.504 inches
End Application:
4920-01-227-0849 servocylinder test stand for f/a-18a and tf/a-18a aircraft
Mounting Facility Thread Direction:
Right-hand
Design Type:
Reusable
Tempurature Rating:
Between 14.0 degrees fahrenheit and 212.0 degrees fahrenheit
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
4568.0 pounds per square inch
Filtering Media Design:
Molded single filtering media response
First Intake Connection Type:
Plain face flange head
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Flange Shape Style:
Rectangular w/threaded bolt holes
First Intake Flange Face Style:
Plain
First Intake Flange Thickness:
2.990 inches
First Intake Flange Length:

4.094 inches

## NSN 4330-01-356-6877

Fluid Filter - Page 2 of 2



First Intake Flange Width:
3.150 inches
Filtering System For Which Designed:
Full flow
Special Features:
Inlet/outlet are on a manifold type connection
Material:
Stainless steel sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000