NSN 4330-01-357-2517

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-357-2517

Mounting Type:

Inlet connection head side and outlet connection head side

Body Outside Diameter:

4.750 inches

Body Height:

11.310 inches

Filtration Rating In Microns:

5.0

Drop Pressure:

10.0 pounds per square inch

Differential Pressure:

100.0 pounds per square inch

End Application:

4310-01-113-8271 compressor unit, reciprocating

Design Type:

Reusable

Tempurature Rating:

150.0 degrees fahrenheit

Features Provided:

Drain cock and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

250.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

1.000 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

For primary oil removal from compressed air; 125scfm; w/o sight glass; auto drain 1/8nptf

Material:

Aluminum bodyaluminum container/cartridgeplastic polyurethane filtering medium and fiber filtering mediumrubber synthetic seal and rubber

buna n seal

NSN 4330-01-357-2517

Fluid Filter - Page 2 of 2

Media For Which Designed:

Air

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000

