

View Online at <https://aerobasegroup.com/nsn/4330-01-357-2518>

Mounting Type:

Inlet connection bottom and outlet connection bottom and threaded hole bottom

Mounting Hole Quantity:

4

Body Outside Diameter:

4.125 inches

Body Height:

13.976 inches

Filtration Rating In Microns:

12.0 absolute

Differential Pressure:

4500.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 3.438 inches and 3.938 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Plain face flange bottom

Mounting Facility Thread Size:

0.438 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Recessed

First Intake Flange Thickness:

0.360 inches

First Intake Flange Length:

4.780 inches

First Intake Flange Width:

4.562 inches

First Intake Flange Recess Diameter:

1.125 inches

First Intake Flange Recess Depth:

0.125 inches

Filtering System For Which Designed:

Full flow

Special Features:

Manifold mounting

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture

Surface Treatment:

Phosphate body and oxide body

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000