

View Online at <https://aerobasegroup.com/nsn/4330-01-357-2518>

**Mounting Type:**

Inlet connection bottom and outlet connection bottom and threaded hole bottom

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

4.125 inches

**Body Height:**

13.976 inches

**Filtration Rating In Microns:**

12.0 absolute

**Differential Pressure:**

4500.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

Between 3.438 inches and 3.938 inches

**Mounting Facility Thread Direction:**

Right-hand

**Design Type:**

Reusable

**Temperature Rating:**

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Plain face flange bottom

**Mounting Facility Thread Size:**

0.438 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Flange Shape Style:**

Rectangular w/threaded bolt holes

**First Intake Flange Face Style:**

Recessed

**First Intake Flange Thickness:**

0.360 inches

**First Intake Flange Length:**

4.780 inches

**First Intake Flange Width:**

4.562 inches

**First Intake Flange Recess Diameter:**

1.125 inches

**First Intake Flange Recess Depth:**

0.125 inches

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Manifold mounting

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water/alcohol mixture

**Surface Treatment:**

Phosphate body and oxide body

**Style Designator:**

Unthreaded shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000