

View Online at <https://aerobasegroup.com/nsn/4330-01-358-8646>

Thread Direction:

Right-hand

Mounting Type:

Unthreaded hole head side

Mounting Hole Diameter:

0.400 inches

Mounting Hole Quantity:

2

Second End Thread Direction:

Right-hand

Body Outside Diameter:

5.000 inches

Body Height:

13.970 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

10.0 pounds per square inch

Differential Pressure:

150.0 pounds per square inch

Distance Between Mounting Hole Centers:

2.250 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Nonreusable

Temperature Rating:

Between -20.0 degrees fahrenheit and 350.0 degrees fahrenheit

Features Provided:

By-pass valve

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.875 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

1/8in. Npt pressure drop ports; 1/4in. Fnpt bottom of filter bowl

Material:

Aluminum body stainless steel filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000