
NSN 4330-01-359-0659

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole head

Mounting Hole Quantity:

2

Body Outside Diameter:

4.620 inches

Body Height:

8.970 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

15.0 pounds per square inch

Differential Pressure:

240.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

Design Type:

Nonreusable

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

60.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.500 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Discharge Thread Series Designator:

Nptf

First Intake Thread Size:

1.062 inches

First Discharge Thread Size:

1.062 inches

First Intake Thread Direction:

Right-hand



NSN 4330-01-359-0659

Fluid Filter - Page 2 of 2



First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

25 psi bypass

Material:

Paper filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture

Style Designator:

Threaded shell (mason jar)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000