## NSN 4330-01-359-0659

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-359-0659

Mounting Type:
Threaded hole head
Mounting Hole Quantity:
2
Body Outside Diameter:
4.620 inches
Body Height:
8.970 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
15.0 pounds per square inch
Differential Pressure:
240.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.120 inches
Design Type:
Nonreusable
Features Provided:
By-pass valve and differential pressure indicator
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
60.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.500 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Discharge Thread Series Designator:
Nptf
First Intake Thread Size:
1.062 inches
1.662 Inches
First Discharge Thread Size:

Right-hand

## NSN 4330-01-359-0659

Fluid Filter - Page 2 of 2



First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
25 psi bypass
Material:
Paper filtering medium
Media For Which Designed:
Fuel/oil, hydrocarbon and water/alcohol mixture
Style Designator:
Threaded shell (mason jar)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000