NSN 4330-01-360-2448

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-360-2448

Mounting Type:
Unthreaded hole back
Mounting Hole Diameter:
0.440 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
4.000 inches
Body Height:
9.750 inches
Filtration Rating In Microns:
10.0
Differential Pressure:
30.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.440 inches and 3.940 inches
Design Type:
Reusable
Tempurature Rating:
225.0 degrees fahrenheit
Features Provided:
Differential pressure indicator and by-pass valve
Filtering Element Quantity:
1
Maximum Operating Pressure:
5000.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe back
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
1.000 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
4.880in. By 4.440in. Porting base manifold type design w/ thd shell and thd cover cap; pointer type dirt indicator located on base;

NSN 4330-01-360-2448

Fluid Filter - Page 2 of 2



			-
RΛ	late	ria	
IV	ale	:110	ı .

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000