NSN 4330-01-360-2448

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-360-2448

Mounting Type:				
Unthreaded hole back				
Mounting Hole Diameter:				
0.440 inches				
Mounting Hole Quantity:				
4				
Body Outside Diameter:				
4.000 inches				
Body Height:				
9.750 inches				
Filtration Rating In Microns:				
10.0				
Differential Pressure:				
30.0 pounds per square inch				
Distance Between Mounting Hole Centers:				
3.440 inches and 3.940 inches				
Design Type:				
Reusable				
Tempurature Rating:				
225.0 degrees fahrenheit				
Features Provided:				
Differential pressure indicator and by-pass valve				
Filtering Element Quantity:				
1				
Maximum Operating Pressure:				
5000.0 pounds per square inch				
Filtering Media Design:				
Pleated single filtering media response				
First Intake Connection Type:				
Threaded internal pipe back				
First Discharge Connection Relationship To Intake Connection:				
Identical to first intake connection				
First Intake Thread Series Designator:				
Nptf				
First Intake Thread Size:				
1.000 inches				
First Intake Thread Direction:				
Right-hand				
Filtering System For Which Designed:				
Full flow				
Special Features:				
4.880in. By 4.440in. Porting base manifold type design w/ thd shell and thd cover cap; pointer type dirt indicator located on base;				

NSN 4330-01-360-2448

Fluid Filter - Page 2 of 2



			-
ΝЛ	late	ria	
IVI	ale	:110	ı .

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000