NSN 4330-01-360-2449

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-360-2449 |
|---|
| Mounting Type: |
| Inlet connection head side and outlet connection head side |
| Body Outside Diameter: |
| 2.750 inches |
| Body Height: |
| 8.110 inches |
| Filtration Rating In Microns: |
| 0.1 absolute |
| Drop Pressure: |
| 10.0 pounds per square inch |
| Differential Pressure: |
| 15.0 pounds per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| 150.0 degrees fahrenheit |
| Features Provided: |
| Differential pressure indicator and drain plug |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Filtering Media Design: |
| Molded all filtering media responses |
| First Intake Connection Type: |
| Threaded internal pipe head side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Nptf |
| First Intake Thread Size: |
| 0.375 inches |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Material: |
| Aluminum body or zinc bodyfiber synthetic filtering medium and plastic polyurethane filtering mediumrubber synthetic seal and rubber buna n |
| sealzinc sediment bowl |
| Media For Which Designed: |
| Air |

Style Designator:

High pressure threaded body

NSN 4330-01-360-2449

Fluid Filter - Page 2 of 2



| Supplementa | ary Features: |
|-------------|---------------|
|-------------|---------------|

Wall mounting bracket p/n5203-02 available but not included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000