

View Online at <https://aerobasegroup.com/nsn/4330-01-360-4456>

**Mounting Type:**

Bracket w/drilled hole top side

**Mounting Hole Diameter:**

0.688 inches

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

36.500 inches

**Body Height:**

63.125 inches

**Distance Between Mounting Hole Centers:**

4.500 inches and 35.000 inches

**End Application:**

Fairbanks-morse 8 cyl 38d8-1/8 engine at 720rpm and 900rpm

**Design Type:**

Reusable

**Temperature Rating:**

199.0 degrees fahrenheit

**Features Provided:**

Drain plug

**Bracket Quantity:**

2

**Filtering Element Quantity:**

3

**Filtering Media Design:**

Cellular single filtering media response

**First Intake Connection Type:**

Plain face flange end

**First Discharge Connection Relationship To Intake Connection:**

Not identical

**First Discharge Connection Type:**

Plain face flange bottom side

**First Intake Flange Outside Diameter:**

23.500 inches

**First Intake Flange Shape Style:**

Round w/unthreaded bolt holes

**First Discharge Flange Shape Style:**

Round w/unthreaded bolt holes

**First Discharge Flange Outside Diameter:**

21.250 inches

**First Intake Flange Face Style:**

Plain

**First Discharge Flange Face Style:**

Plain

**First Intake Flange Thickness:**

1.000 inches

**First Discharge Flange Thickness:**

1.000 inches

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Barrel-type shaped inlet on one end and removable cover on other; outlet on bottom, 41.250in. From inlet, outlet flange has 16ea. 3/4in. Holes on 19.250in. B.C.; inlet flange has 16ea 3/4in.Holes on 21.250in. B.C.; 2 brackets welded on top; filters 1-nom 20-20 and 2 nom 16-20 elements; cover clamped with 3 threaded j-hook locking devices w/ wing nuts located 120.0deg apart around rim; filter meets mil-f-7194; finished w/magnacoat cp-211 (black); unit designed for navy high-shock condition

**Material:**

Metal body

**Media For Which Designed:**

Air

**Surface Treatment:**

Paint body

**Style Designator:**

Split body (loop or rim clamp)

**Supplementary Features:**

Requires 4 unit per installation

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000