

View Online at <https://aerobasegroup.com/nsn/4330-01-360-7985>

Mounting Type:

Threaded hole head

Mounting Hole Quantity:

4

Body Outside Diameter:

4.000 inches

Body Height:

11.930 inches

Drop Pressure:

5.0 pounds per square inch

Differential Pressure:

25.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.380 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

1.000 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Cast alum head; 9.0in.Long spin-on type filter w/rigid steel attachment plate; visual indicator w/lh location; mtg holes 3/8-16unc-2b x 0.50in.Dp

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000