NSN 4330-01-361-2402

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-361-2402

Mounting Type: Inlet connection line and outlet connection lineinlet connection side near top and outlet connection side near top Body Length: 6.570 inches Body Height: 15.160 inches Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Body Length: 6.570 inches Body Height: 15.160 inches Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
6.570 inches Body Height: 15.160 inches Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Body Height: 15.160 inches Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Design Type: Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Limited Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Tempurature Rating: Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Features Provided: By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
By-pass valve Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
6000.0 pounds per square inch First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
First Intake Connection Type: Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Threaded internal pipe linethreaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Identical to first intake connection
Distance From Bottom Of Body To Center Of Inlet:
13.020 inches
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.875 inches
First Intake Thready Qty Per Inch (tpi):
12
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
rated flow 80 gpm; by-pass valve 50 psid
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Straight flow basket strainer w/bolted cover
Shelf Life:
N/a

--

Unit Of Measure:

NSN 4330-01-361-2402

Fluid Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A24000