

View Online at <https://aerobasegroup.com/nsn/4330-01-366-0745>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.531 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

6.000 inches

Body Height:

Between 19.885 inches and 20.110 inches

Differential Pressure:

35.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.500 inches

Design Type:

Reusable

Features Provided:

Differential pressure indicator and differential pressure relief valve and drain plug and air bleed valve

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.625 inches

First Intake Thread Qty Per Inch (tpi):

28

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Relief valve cracking pressure, 150.0 psi; sediment bowl is heat treated; filter element is not provided

Material:

Stainless steel sediment bowl

Material Specification:

Mil-r-83248, class 1 military specification single material response seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000

Mil-std (military Standard):

Mil-r-83248 spec.