

View Online at <https://aerobasegroup.com/nsn/4330-01-366-0745>

**Mounting Type:**

Unthreaded hole head

**Mounting Hole Diameter:**

0.531 inches

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

6.000 inches

**Body Height:**

Between 19.885 inches and 20.110 inches

**Differential Pressure:**

35.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

4.500 inches

**Design Type:**

Reusable

**Features Provided:**

Differential pressure indicator and differential pressure relief valve and drain plug and air bleed valve

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.625 inches

**First Intake Thread Qty Per Inch (tpi):**

28

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Relief valve cracking pressure, 150.0 psi; sediment bowl is heat treated; filter element is not provided

**Material:**

Stainless steel sediment bowl

**Material Specification:**

Mil-r-83248, class 1 military specification single material response seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000

**Mil-std (military Standard):**

Mil-r-83248 spec.