## NSN 4330-01-366-3889

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-366-3889

view Offiline at https://acrobasegroup.com/hsh/4550-01-500-5005
Mounting Type:
Inlet connection line and outlet connection line
Body Outside Diameter:
4.000 inches
Body Height:
8.500 inches
Filtration Rating In Microns:
7.2 absolute
Differential Pressure:
150.0 pounds per square inch
Design Type:
Reusable
Tempurature Rating:
225.0 degrees fahrenheit and -45.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator and drain plug and thermal lockout
Bracket Quantity:
1
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
First Intake Connection Type:
Threaded internal pipe head
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.000 inches
First Intake Thready Qty Per Inch (tpi):
16
First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Pop-up indicator w/thermal lock-out, bowl black anodized w/knurled bands

Material:

Rubber buna n seal

## **NSN 4330-01-366-3889** Fluid Filter - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon
Surface Treatment:
Anodize body
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A24000