NSN 4330-01-366-5664

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-366-5664

Mounting Type:

Threaded hole head

Mounting Hole Quantity:

4

Body Outside Diameter:

Between 3.270 inches and 3.580 inches

Body Height:

6.620 inches

Filtration Rating In Microns:

10.0 absolute

Differential Pressure:

3045.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 1.260 inches and 2.205 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Tempurature Rating:

Between 14.0 degrees fahrenheit and 212.0 degrees fahrenheit

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unf

Maximum Operating Pressure:

1450.0 pounds per square inch

Filtering Media Design:

Spun roving single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.250 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

NSN 4330-01-366-5664

Fluid Filter - Page 2 of 2



First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

W/o clog indicator; w/o by-pass valve

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000