## NSN 4330-01-366-5664

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-366-5664 **Mounting Type:** Threaded hole head **Mounting Hole Quantity: Body Outside Diameter:** Between 3.270 inches and 3.580 inches **Body Height:** 6.620 inches **Filtration Rating In Microns:** 10.0 absolute **Differential Pressure:** 3045.0 pounds per square inch **Distance Between Mounting Hole Centers:** Between 1.260 inches and 2.205 inches **Mounting Facility Thread Direction:** Right-hand **Design Type:** Reusable **Tempurature Rating:** Between 14.0 degrees fahrenheit and 212.0 degrees fahrenheit **Filtering Element Quantity:** 1 **Mounting Facility Thread Series Designator: Maximum Operating Pressure:** 1450.0 pounds per square inch Filtering Media Design: Spun roving single filtering media response **First Intake Connection Type:** Threaded internal tube head side **Mounting Facility Thread Size:** 0.250 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Un First Intake Thread Size: 1.062 inches First Intake Thready Qty Per Inch (tpi):

12 First Intake Thread Class:

2b

## NSN 4330-01-366-5664

Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
W/o clog indicator; w/o by-pass valve
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A24000