## NSN 4330-01-366-9430

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-366-9430
Mounting Type:
Inlet connection head side and outlet connection head side
Body Outside Diameter:
4.750 inches
Body Height:
13.270 inches
Filtration Rating In Microns:
5.0
Drop Pressure:
10.0 pounds per square inch
Differential Pressure:
100.0 pounds per square inch
End Application:
Air compressor units
Design Type:
Reusable
Tempurature Rating:
150.0 degrees fahrenheit
Features Provided:
Differential pressure indicator and drain plug
Filtering Element Quantity:
1
Maximum Operating Pressure:
250.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe head
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
1.000 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
With sight glass; manual drain petcock, 125 scfm
Material:

Aluminum bodyfiber filtering medium and plastic polyurethane filtering mediumrubber buna n sealaluminum sediment bowl and glass sediment bowl

## NSN 4330-01-366-9430

Fluid Filter - Page 2 of 2

A24000



Media For Which Designed:
Air
Style Designator:
High pressure threaded body
Supplementary Features:
For primary removal of oil from compressed air
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: