## NSN 4330-01-367-4947

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-367-4947

view Offilite at https://defobasegroup.com/hsr//4000-01-30/-404/
Mounting Type:
Inlet connection head side and outlet connection head side
Body Outside Diameter:
2.750 inches
Body Height:
8.940 inches
Filtration Rating In Microns:
0.10
Drop Pressure:
10.0 pounds per square inch
Differential Pressure:
10.0 pounds per square inch
Design Type:
Reusable
Tempurature Rating:
150.0 degrees fahrenheit
Features Provided:
Differential pressure indicator and drain plug
Filtering Element Quantity:
1
Maximum Operating Pressure:
250.0 pounds per square inch
Filtering Media Design:
Molded single filtering media response
First Intake Connection Type:
Threaded internal pipe head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
0.375 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
With sight glass; manual drain; element polyurethane foam
Material:

Zinc body or aluminum bodyfiber synthetic filtering medium and plastic polyurethane filtering mediumrubber synthetic seal and rubber buna n

Media For Which Designed:

sealzinc sediment bowl

Air

## NSN 4330-01-367-4947

Fluid Filter - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000