NSN 4330-01-369-4943

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-369-4943

| Mounting Type: |
|--|
| Inlet connection head side and outlet connection head side |
| Body Outside Diameter: |
| 2.630 inches |
| Body Height: |
| 4.500 inches |
| Filtration Rating In Microns: |
| Not rated |
| Drop Pressure: |
| 5.0 pounds per square inch |
| Differential Pressure: |
| Not rated |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| 100.0 degrees fahrenheit |
| Features Provided: |
| Drain plug |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 100.0 pounds per square inch |
| Filtering Media Design: |
| Any acceptable single filtering media response |
| First Intake Connection Type: |
| Threaded internal pipe head side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Npt |
| First Intake Thread Size: |
| 0.500 inches |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Special Features: |
| Ithree piece design with 316ss head and end cap, pyrex glass body (cylindrical shaped, open both end) with plastic bowl guard linked |
| together with center tie-rod; bottom end cap has 1/8in npt manual drain |
| Material: |
| Steel comp 316 bodyglass container/cartridgerubber synthetic seal |

Air

Media For Which Designed:

NSN 4330-01-369-4943

Fluid Filter - Page 2 of 2



| • | _ | | |
|-------|-----|------|--------|
| Style | De: | sıar | nator: |
| , | | 9.9. | |

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000