NSN 4330-01-370-6112

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-370-6112 |
|--|
| Mounting Type: |
| Inlet connection bottom side and outlet connection bottom side |
| Body Outside Diameter: |
| 6.120 inches |
| Body Height: |
| 15.240 inches |
| Differential Pressure: |
| 150.0 pounds per square inch |
| Design Type: |
| Nonreusable |
| Tempurature Rating: |
| Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| First Intake Connection Type: |
| Threaded internal tube bottom side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Un |
| First Intake Thread Size: |
| 1.875 inches |
| First Intake Thready Qty Per Inch (tpi): |
| 12 |
| First Intake Thread Class: |
| 2b |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| By-pass flow |
| Material: |
| Steel comp 1018 sediment bowl |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Style Designator: |
| Unthreaded shell |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 4330-01-370-6112

Fluid Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A24000