

View Online at <https://aerobasegroup.com/nsn/4330-01-373-2791>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

6

Body Outside Diameter:

6.100 inches

Body Height:

15.030 inches

Filtration Rating In Microns:

3.00 absolute and 5.00

Differential Pressure:

73.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.970 inches and 1.970 inches and 2.200 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Features Provided:

Differential pressure indicator and by-pass valve

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Layered single filtering media response

First Intake Connection Type:

Raised face flange head side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Raised

Filtering System For Which Designed:

Full flow

Special Features:

Visual indicator; hex wrenching device located on bottom; ports 1-1/2in.Sae flange, 4 holes 13 unc x 0.7in.Dp; mtg holes 3/8-16unc-28 x 0.39in.Dp; head across ports 6.10in.W, head 5.67in.Dia, bowl 4.80in.Dia

Material:

Steel body

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Supplementary Features:

Normal flow (without reverse flow feature)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000