NSN 4330-01-375-8138

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-375-8138

Mounting Type:

Unthreaded hole head side

Mounting Hole Diameter:

0.345 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

3.750 inches

Body Height:

7.850 inches

Filtration Rating In Microns:

5.0

Drop Pressure:

5.0 pounds per square inch

Differential Pressure:

300.0 pounds per square inch

Distance Between Mounting Hole Centers:

2.000 inches

End Application:

W/s code 19, f15e ac

Design Type:

Reusable

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

5000.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

0.500 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

NSN 4330-01-375-8138

Fluid Filter - Page 2 of 2



Special Features:

El"o" ring and hsg"o" ring made of nitrile

Material:

Aluminum alloy 2024 bodyglass filtering mediumrubber synthetic seal

Style Designator:

Threaded shell (mason jar)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000