

View Online at <https://aerobasegroup.com/nsn/4330-01-383-2290>

**Mounting Type:**

Inlet connection head side and outlet connection head side

**Mounting Hole Diameter:**

0.250 inches

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

85.850 millimeters

**Body Height:**

288.54 millimeters

**Filtration Rating In Microns:**

10.0

**Differential Pressure:**

50.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

38.100 millimeters and 73.152 millimeters

**Mounting Facility Thread Direction:**

Right-hand

**Design Type:**

Reusable

**Temperature Rating:**

Between -50.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and drain plug

**Bracket Quantity:**

1

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Filtering Media Design:**

Spun single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.250 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Hex drain facility on bottom; dirt capaci type 11.0gram; mtg holes 0.25-20unc-2b x 0.34in. Min full thd; str thd boss port per sae j514

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000