

View Online at <https://aerobasegroup.com/nsn/4330-01-383-5475>

Mounting Type:

Outlet connection bottom

Body Outside Diameter:

8.360 inches

Body Height:

28.880 inches

Filtration Rating In Microns:

25.0

Differential Pressure:

500.0 pounds per square inch

Design Type:

Reusable

Tempurature Rating:

Between -20.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

350.0 pounds per square inch

Filtering Media Design:

Porous single filtering media response

First Intake Connection Type:

Threaded internal pipe side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

External butt weld bottom

First Discharge Outside Diameter:

5.250 inches

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

2.500 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Intank mounting, 6.00 in. Diameter hole req.; 13.50 in. Clearance req. For element replacement

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000