## NSN 4330-01-383-5475

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-383-5475

Mounting Type:
Outlet connection bottom
Body Outside Diameter:
8.360 inches
Body Height:
28.880 inches
Filtration Rating In Microns:
25.0
Differential Pressure:
500.0 pounds per square inch
Design Type:
Reusable
Tempurature Rating:
Between -20.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
Air bleed valve and by-pass valve and differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
350.0 pounds per square inch
Filtering Media Design:
Porous single filtering media response
First Intake Connection Type:
Threaded internal pipe side
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
External butt weld bottom
First Discharge Outside Diameter:
5.250 inches
First Intake Thread Series Designator:
Npt
First Intake Thread Size:
2.500 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Intank mounting, 6.00 in. Diameter hole req.; 13.50 in. Clearance req. For element replacement
Material:

Steel container/cartridge

## NSN 4330-01-383-5475

Fluid Filter - Page 2 of 2



Media For Which Designe	ed:
-------------------------	-----

Fuel/oil, hydrocarbon

Style Designator:

Unthreaded shell

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A24000