

View Online at <https://aerobasegroup.com/nsn/4330-01-385-1266>

Mounting Type:

Outlet connection top and threaded hole top

Mounting Hole Quantity:

4

Body Outside Diameter:

8.580 inches

Body Height:

19.830 inches

Filtration Rating In Microns:

6.0

Differential Pressure:

150.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.406 inches and 2.750 inches

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

6000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Plain face flange head side

Mounting Facility Thread Size:

0.500 inches

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Plain face flange top

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Discharge Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Discharge Flange Face Style:

Plain

First Intake Flange Thickness:

1.060 inches

First Discharge Flange Thickness:

1.060 inches

First Intake Flange Length:

6.250 inches

Err Default:

Err default

First Intake Flange Width:

2.875 inches

Err Default:

Err default

Filtering System For Which Designed:

Full flow

Special Features:

Ports: 2.0in. Split-flange sae j518c

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon or water or water/alcohol mixture

Surface Treatment:

Phosphate body

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000